



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/600,003	07/10/2000	HAJIME INOUE	SONYJP-086	6725

530 7590 01/26/2005

LERNER, DAVID, LITTENBERG,  
KRUMHOLZ & MENTLIK  
600 SOUTH AVENUE WEST  
WESTFIELD, NJ 07090

EXAMINER

MANNING, JOHN

ART UNIT	PAPER NUMBER
----------	--------------

2614

DATE MAILED: 01/26/2005

Please find below and/or attached an Office communication concerning this application or proceeding.

## Office Action Summary

Application No.

09/600,003

Applicant(s)

INOUE ET AL.

Examiner

John Manning

Art Unit

2614

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --  
Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If the period for reply specified above is less than thirty (30) days, a reply within the statutory minimum of thirty (30) days will be considered timely.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

### Status

- 1) ☒ Responsive to communication(s) filed on 04 August 2004.
- 2a) ☐ This action is FINAL. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

### Disposition of Claims

- 4) ☒ Claim(s) 31-72 is/are pending in the application.
- 4a) Of the above claim(s) \_\_\_\_\_ is/are withdrawn from consideration.
- 5) ☐ Claim(s) \_\_\_\_\_ is/are allowed.
- 6) ☒ Claim(s) 31-72 is/are rejected.
- 7) ☐ Claim(s) \_\_\_\_\_ is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

### Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on \_\_\_\_\_ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.  
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).  
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

### Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some \* c) ☐ None of:
- ☐ Certified copies of the priority documents have been received.
  - ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.
  - ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

\* See the attached detailed Office action for a list of the certified copies not received.

### Attachment(s)

- 1) ☒ Notice of References Cited (PTO-892)
- 2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)
- 3) ☒ Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)  
Paper No(s)/Mail Date 11/15/04
- 4) ☐ Interview Summary (PTO-413)  
Paper No(s)/Mail Date. \_\_\_\_\_
- 5) ☐ Notice of Informal Patent Application (PTO-152)
- 6) ☐ Other: \_\_\_\_\_

10/04/04

## **DETAILED ACTION**

### ***Response to Arguments***

1. Applicant's arguments with respect to claims 31-34, 40-52 and 58-72 have been considered but are moot in view of the new ground(s) of rejection.

Applicant's arguments, see Page 15, filed 8/09/2004, with respect to the rejection(s) of claim(s) 35-39 under 35 U.S.C 102(a) have been fully considered and are persuasive. Therefore, the rejection has been withdrawn. However, upon further consideration, a new ground(s) of rejection is made in view of Lenihan et al. (US Pat No 6,169,843) and further in view of Chihara (US Pat No 6,678,462).

### ***Claim Rejections - 35 USC § 103***

2. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

3. Claims 31-33, 40-44, 46-49, 51-52, 58-60, 62-65 and 67-72 are rejected under 35 U.S.C. 103(a) as being unpatentable over Browne et al. (International Publication Number WO 92/22983) in view of Lenihan et al. and further in view of Chihara.

In regard to claim 31, Brown et al. discloses a large capacity, random access, multi-source audio and video recorder player which is capable of receiving a plurality of simultaneous input signals and which allows a user to view

Art Unit: 2614

and/or record selected ones of the plurality of input signals. "The multi-source recorder player 100 preferably has multiple input connections, each of which may receive an input signal 101a-101f from air and ground based broadcast sources, cable feeds, or digital distribution sources" (Page 6). The claimed decoder can be met by met by the A/D converter 102, the compressors 103, the decompressors 106 or the D/A converters 110. The reference discloses many digital interfaces, most notably digital outputs 112g and 112 h in combination with the controller 105 and the interface 105a. "There are two digital output 112g and 112h. Output 112g may be used for sending decompressed digital data, for example, to a digital television receiver" (Page 16). The controller 105 meets the claimed "display processing circuit for displaying information associated with a program recorded on a recording medium loaded in said reproducing apparatus by a predetermined format". "Controller 105 is a microprocessor which preferably runs a user control program and allows a user to access and control the multi-source recorder player 100" (Page 13). "Of the three analog outputs, output 112a may be set by default in the setup page 300, shown in Fig. 3, to receive the control screens which are described below with respect to the user control section shown in Figs. 2-11" (Page 16). The source column in the stored program list screen 600 shown in Figure 6 indicates the originating source of the signal. Although not displayed in Figure 6, DBS (direct broadcast satellite) is a selectable source. DBS indicates a digital signal. The DBS signal is intrinsically is compressed and multiplexed. Browne fails to explicitly disclose "a digital interface for receiving the transport stream from an external reproducing

Art Unit: 2614

apparatus". Lenihan teaches the "a digital interface for receiving the transport stream from an external reproducing apparatus" so as to allow different type of storage to be used (Figure 2; Col 5, Lines 58-67; Col 6, Lines 1-7).

Consequently, it would have been obvious to one of ordinary skill in the art to modify Browne with the "a digital interface for receiving the transport stream from an external reproducing apparatus" so as to allow different type of storage to be used. The combined teaching of Browne and Lenihan fails to explicitly disclose displaying a message indicating the mode of the recorded program. Chihara teaches displaying information of the mode of the recorded program so as to provide the user with information regarding the recording (Figure 9, Col 7, Lines 21-31). Consequently, it would have been obvious to one of ordinary skill in the art to modify the combined teaching with displaying information of the mode of the recorded program so as to provide the user with information regarding the recording.

Claim 32 is met by the stored program list screen 600 illustrated in Figure 6. It is noted that the examiner interprets the claim to be written in the alternative, such that a channel number, a program name, a genre, a date of the recording, or a recording time may meet the claimed limitation. The stored program list screen 600 clearly shows the channel number, the program name, date of the recording, and the recording time.

In regard to claim 33, the recording position is inherent to the information displayed. In order for the programs to be retrieved, there must there be position information.

Art Unit: 2614

Claim 40 is met by that discussed above for claim 31.

In regard to claim 41, Brown et al. discloses a large capacity, random access, multi-source audio and video recorder player which is capable of receiving a plurality of simultaneous input signals and which allows a user to view and/or record selected ones of the plurality of input signals. "The multi-source recorder player 100 preferably has multiple input connections, each of which may receive an input signal 101a-101f from air and ground based broadcast sources, cable feeds, or digital distribution sources" (Page 6). The claimed decoder can be met by the A/D converter 102, the compressors 103, the decompressors 106 or the D/A converters 110. The reference discloses many digital interfaces in combination with the controller 105 and the interface 105a, most notably digital outputs 112g and 112h. "There are two digital output 112g and 112h. Output 112g may be used for sending decompressed digital data, for example, to a digital television receiver" (Page 16). The controller 105 meets the claimed "display processing circuit for displaying information associated with a program recorded on a recording medium loaded in said reproducing apparatus by a predetermined format". "Controller 105 is a microprocessor which preferably runs a user control program and allows a user to access and control the multi-source recorder player 100" (Page 13). "Of the three analog outputs, output 112a may be set by default in the setup page 300, shown in Fig. 3, to receive the control screens which are described below with respect to the user control section shown in Figs. 2-11" (Page 16). The source column in the stored program list screen 600 shown in Figure 6 indicates the originating source of the

Art Unit: 2614

signal. The analog output is met by outputs 112a-c. "Of the three analog outputs, output 112a may be set by default in the setup page 300, shown in Fig. 3, to receive the control screens which are described below with respect to the user control section shown in Figs. 2-11" (Page 16). Browne fails to explicitly disclose "a digital interface for receiving the transport stream from an external reproducing apparatus". Lenihan teaches the "a digital interface for receiving the transport stream from an external reproducing apparatus" so as to allow different type of storage to be used (Figure 2; Col 5, Lines 58-67; Col 6, Lines 1-7).

Consequently, it would have been obvious to one of ordinary skill in the art to modify Browne with the "a digital interface for receiving the transport stream from an external reproducing apparatus" so as to allow different type of storage to be used. The combined teaching of Browne and Lenihan fails to explicitly disclose displaying a message indicating the mode of the recorded program. Chihara teaches displaying information of the mode of the recorded program so as to provide the user with information regarding the recording (Figure 9, Col 7, Lines 21-31). Consequently, it would have been obvious to one of ordinary skill in the art to modify the combined teaching with displaying information of the mode of the recorded program so as to provide the user with information regarding the recording.

In regard to claim 42, the aforementioned combined teaching discloses a large capacity, random access, multi-source audio and video recorder player which is capable of receiving a plurality of simultaneous input signals and which allows a user to view and/or record selected ones of the plurality of input signals.

Art Unit: 2614

The combined teaching fails to explicitly disclose the displaying of an alarm or "message" if the user selects an input/out that is inconsistent with the mode of the recorder/reproducer. However, it is submitted that it would have been clearly obvious to one of ordinary skill in the art to modify the combined teaching with the displaying of an alarm or "message" if the user selects an input/out that is inconsistent with the mode of the recorder/reproducer so as to notify the user of any problem that may arise in program recording/reproduction.

Claim 43 is met by the stored program list screen 600 illustrated in Figure 6. It is noted that the examiner interprets the claim to be written in the alternative, such that a channel number, a program name, a genre, a date of the recording, or a recording time may meet the claimed limitation. The stored program list screen 600 clearly shows the channel number, the program name, date of the recording, and the recording time.

In regard to claim 44, the recording position is inherent to the information displayed. In order for the programs to be retrieved, there must there be position information.

Claim 46 is met by that discussed above for claim 41.

In regard to claim 47, Brown et al. discloses a large capacity, random access, multi-source audio and video recorder player which is capable of receiving a plurality of simultaneous input signals and which allows a user to view and/or record selected ones of the plurality of input signals. "The multi-source recorder player 100 preferably has multiple input connections, each of which may receive an input signal 101a-101f from air and ground based broadcast sources,



Art Unit: 2614

cable feeds, or digital distribution sources” (Page 6). The claimed decoder can be met by met by the A/D converter 102, the compressors 103, the decompressors 106 or the D/A converters 110. The reference discloses many digital interfaces, most notably digital outputs 112g and 112 h in combination with the controller 105 and the interface 105a. “There are two digital output 112g and 112h. Output 112g may be used for sending decompressed digital data, for example, to a digital television receiver” (Page 16). The controller 105 meets the claimed “display processing circuit for displaying information associated with a program recorded on a recording medium loaded in said reproducing apparatus by a predetermined format”. “Controller 105 is a microprocessor which preferably runs a user control program and allows a user to access and control the multi-source recorder player 100” (Page 13). “Of the three analog outputs, output 112a may be set by default in the setup page 300, shown in Fig. 3, to receive the control screens which are described below with respect to the user control section shown in Figs. 2-11” (Page 16). The source column in the stored program list screen 600 shown in Figure 6 indicates the originating source of the signal. Although not displayed in Figure 6, DBS (direct broadcast satellite) is a selectable source. DBS indicates a digital signal. The DBS signal is intrinsically is compressed and multiplexed. Browne fails to explicitly disclose “a digital interface for receiving the transport stream from an external reproducing apparatus”. Lenihan teaches the “a digital interface for receiving the transport stream from an external reproducing apparatus” so as to allow different type of storage to be used (Figure 2; Col 5, Lines 58-67; Col 6, Lines 1-7).

Art Unit: 2614

Consequently, it would have been obvious to one of ordinary skill in the art to modify Browne with the "a digital interface for receiving the transport stream from an external reproducing apparatus" so as to allow different type of storage to be used. The combined teaching of Browne and Lenihan fails to explicitly disclose displaying a message indicating the mode of the recorded program. Chihara teaches displaying information of the mode of the recorded program so as to provide the user with information regarding the recording (Figure 9, Col 7, Lines 21-31). Consequently, it would have been obvious to one of ordinary skill in the art to modify the combined teaching with displaying information of the mode of the recorded program so as to provide the user with information regarding the recording.

Claim 48 is met by the stored program list screen 600 illustrated in Figure 6. It is noted that the examiner interprets the claim to be written in the alternative, such that a channel number, a program name, a genre, a date of the recording, or a recording time may meet the claimed limitation. The stored program list screen 600 clearly shows the channel number, the program name, date of the recording, and the recording time.

In regard to claim 49, the recording position is inherent to the information displayed. In order for the programs to be retrieved, there must there be position information.

Claim 51 is met by that discussed above for claim 47.

In regard to claim 52, Brown et al. discloses a large capacity, random access, multi-source audio and video recorder player which is capable of

Art Unit: 2614

receiving a plurality of simultaneous input signals and which allows a user to view and/or record selected ones of the plurality of input signals. "The multi-source recorder player 100 preferably has multiple input connections, each of which may receive an input signal 101a-101f from air and ground based broadcast sources, cable feeds, or digital distribution sources" (Page 6). The claimed decoder can be met by the A/D converter 102, the compressors 103, the decompressors 106 or the D/A converters 110. The reference discloses many digital interfaces, most notably digital outputs 112g and 112h in combination with the controller 105 and the interface 105a. "There are two digital output 112g and 112h. Output 112g may be used for sending decompressed digital data, for example, to a digital television receiver" (Page 16). The controller 105 meets the claimed "display processing circuit for displaying information associated with a program recorded on a recording medium loaded in said reproducing apparatus by a predetermined format". "Controller 105 is a microprocessor which preferably runs a user control program and allows a user to access and control the multi-source recorder player 100" (Page 13). "Of the three analog outputs, output 112a may be set by default in the setup page 300, shown in Fig. 3, to receive the control screens which are described below with respect to the user control section shown in Figs. 2-11" (Page 16). The source column in the stored program list screen 600 shown in Figure 6 indicates the originating source of the signal. Although not displayed in Figure 6, DBS (direct broadcast satellite) is a selectable source. DBS indicates a digital signal. The DBS signal is intrinsically compressed and multiplexed. Another possible selectable source is cable,

Art Unit: 2614

which would indicate an analog signal. The analog output is met by outputs 112a-c. "Of the three analog outputs, output 112a may be set by default in the setup page 300, shown in Fig. 3, to receive the control screens which are described below with respect to the user control section shown in Figs. 2-11" (Page 16). Browne fails to explicitly disclose "a digital interface for receiving the transport stream from an external reproducing apparatus". Lenihan teaches the "a digital interface for receiving the transport stream from an external reproducing apparatus" so as to allow different type of storage to be used (Figure 2; Col 5, Lines 58-67; Col 6, Lines 1-7). Consequently, it would have been obvious to one of ordinary skill in the art to modify Browne with the "a digital interface for receiving the transport stream from an external reproducing apparatus" so as to allow different type of storage to be used. The combined teaching of Browne and Lenihan fails to explicitly disclose displaying a message indicating the mode of the recorded program. Chihara teaches displaying information of the mode of the recorded program so as to provide the user with information regarding the recording (Figure 9, Col 7, Lines 21-31). Consequently, it would have been obvious to one of ordinary skill in the art to modify the combined teaching with displaying information of the mode of the recorded program so as to provide the user with information regarding the recording.

In regard to claim 58, Brown et al. discloses a large capacity, random access, multi-source audio and video recorder player which is capable of receiving a plurality of simultaneous input signals and which allows a user to view and/or record selected ones of the plurality of input signals. "The multi-source

Art Unit: 2614

recorder player 100 preferably has multiple input connections, each of which may receive an input signal 101a-101f from air and ground based broadcast sources, cable feeds, or digital distribution sources" (Page 6). The claimed decoder can be met by met by the A/D converter 102, the compressors 103, the decompressors 106 or the D/A converters 110. The reference discloses many digital interfaces, most notably digital outputs 112g and 112 h in combination with the controller 105 and the interface 105a. "There are two digital output 112g and 112h. Output 112g may be used for sending decompressed digital data, for example, to a digital television receiver" (Page 16). Browne fails to explicitly disclose "displaying a message showing that a recording mode of a program recorded on a recording medium loaded in said reproducing apparatus indicates an analog recording or a digital recording". Chihara teaches displaying information of the mode of the recorded program, which would indicate whether the signal is analog or digital so as to provide the user with information regarding the recording (Figure 9, Col 7, Lines 21-31). Consequently, it would have been obvious to one of ordinary skill in the art to modify Browne with displaying information of the mode of the recorded program so as to provide the user with information regarding the recording. The combined teaching fails to explicitly disclose the displaying of an alarm or "message" if the user selects an input/out that is inconsistent with the mode of the recorder/reproducer. However, it is submitted that it would have been clearly obvious to one of ordinary skill in the art to modify the combined teaching with the displaying of an alarm or "message" if the user selects an input/out that is inconsistent with the mode of the

Art Unit: 2614

recorder/reproducer so as to notify the user of any problem that may arise in program recording/reproduction.

Claim 59 is met by the stored program list screen 600 illustrated in Figure 6. It is noted that the examiner interprets the claim to be written in the alternative, such that a channel number, a program name, a genre, a date of the recording, or a recording time may meet the claimed limitation. The stored program list screen 600 clearly shows the channel number, the program name, date of the recording, and the recording time.

In regard to claim 60, the recording position is inherent to the information displayed. In order for the programs to be retrieved, there must there be position information.

Claim 62 is met by that discussed above for claim 58.

In regard to claim 63, Brown et al. discloses a large capacity, random access, multi-source audio and video recorder player which is capable of receiving a plurality of simultaneous input signals and which allows a user to view and/or record selected ones of the plurality of input signals. "The multi-source recorder player 100 preferably has multiple input connections, each of which may receive an input signal 101a-101f from air and ground based broadcast sources, cable feeds, or digital distribution sources" (Page 6). The claimed decoder can be met by met by the A/D converter 102, the compressors 103, the decompressors 106 or the D/A converters 110. The reference discloses many digital interfaces, most notably digital outputs 112g and 112h in combination with the controller 105 and the interface 105a. "There are two digital output 112g and

Art Unit: 2614

112h. Output 112g may be used for sending decompressed digital data, for example, to a digital television receiver" (Page 16). The controller 105 meets the claimed "display processing circuit for displaying information associated with a program recorded on a recording medium loaded in said reproducing apparatus by a predetermined format". "Controller 105 is a microprocessor which preferably runs a user control program and allows a user to access and control the multi-source recorder player 100" (Page 13). "Of the three analog outputs, output 112a may be set by default in the setup page 300, shown in Fig. 3, to receive the control screens which are described below with respect to the user control section shown in Figs. 2-11" (Page 16). Browne fails to explicitly disclose "displaying a message showing that a recording mode of a program recorded on a recording medium loaded in said reproducing apparatus indicates an analog recording or a digital recording". Chihara teaches displaying information of the mode of the recorded program, which would indicate whether the signal is analog or digital so as to provide the user with information regarding the recording (Figure 9, Col 7, Lines 21-31). Consequently, it would have been obvious to one of ordinary skill in the art to modify Browne with displaying information of the mode of the recorded program so as to provide the user with information regarding the recording. The combined teaching fails to explicitly disclose the displaying of an alarm or "message" if the user selects an input/out that is inconsistent with the mode of the recorder/reproducer. However, it is submitted that it would have been clearly obvious to one of ordinary skill in the art to modify the combined teaching with the displaying of an alarm or "message" if the user

Art Unit: 2614

selects an input/out that is inconsistent with the mode of the recorder/reproducer so as to notify the user of any problem that may arise in program recording/reproduction.

Claim 64 is met by the stored program list screen 600 illustrated in Figure 6. It is noted that the examiner interprets the claim to be written in the alternative, such that a channel number, a program name, a genre, a date of the recording, or a recording time may meet the claimed limitation. The stored program list screen 600 clearly shows the channel number, the program name, date of the recording, and the recording time.

In regard to claim 65, the recording position is inherent to the information displayed. In order for the programs to be retrieved, there must there be position information.

Claim 67 is met by that discussed above for claim 63.

In regard to claim 68, the claimed step of "receiving a digital broadcasting signal constructed by a transport stream in which video data and audio data have been compressed and multiplexed" is met by the received DBS signal. The DBS signal is intrinsically is compressed and multiplexed. The claimed step of "decoding said received digital broadcasting signal" can be met by met by the A/D converter 102, the compressors 103, the decompressors 106 or the D/A converters 110. The claimed step of "receiving the transport stream from a reproducing apparatus through a digital interface" can be met by the many digital interfaces disclosed, most notably digital outputs 112g and 112h in combination with the controller 105 and the interface 105a. "There are two digital output 112g



Art Unit: 2614

and 112h. Output 112g may be used for sending decompressed digital data, for example, to a digital television receiver" (Page 16). The claimed step "displaying a message showing that a recording mode of a program recorded on a recording medium loaded in said reproducing apparatus indicates an analog recording or a digital recording" is met by the controller 105. "Controller 105 is a microprocessor which preferably runs a user control program and allows a user to access and control the multi-source recorder player 100" (Page 13). "Of the three analog outputs, output 112a may be set by default in the setup page 300, shown in Fig. 3, to receive the control screens which are described below with respect to the user control section shown in Figs. 2-11" (Page 16). Browne fails to explicitly disclose "displaying a message showing that a recording mode of a program recorded on a recording medium loaded in said reproducing apparatus indicates an analog recording or a digital recording". Chihara teaches displaying information of the mode of the recorded program, which would indicate whether the signal is analog or digital so as to provide the user with information regarding the recording (Figure 9, Col 7, Lines 21-31). Consequently, it would have been obvious to one of ordinary skill in the art to modify Browne with displaying information of the mode of the recorded program so as to provide the user with information regarding the recording. The combined teaching fails to explicitly disclose the displaying of an alarm or "message" if the user selects an input/out that is inconsistent with the mode of the recorder/reproducer. However, it is submitted that it would have been clearly obvious to one of ordinary skill in the art to modify the combined teaching with the displaying of an alarm or "message" if

Art Unit: 2614

the user selects an input/out that is inconsistent with the mode of the recorder/reproducer so as to notify the user of any problem that may arise in program recording/reproduction.

In regard to claim 69, the claimed step of "receiving a digital broadcasting signal constructed by a transport stream in which video data and audio data have been compressed and multiplexed" is met by the received DBS signal. The DBS signal is intrinsically is compressed and multiplexed. The claimed step of "decoding said received digital broadcasting signal" can be met by met by the A/D converter 102, the compressors 103, the decompressors 106 or the D/A converters 110. The claimed step of "receiving the transport stream from a reproducing apparatus through a digital interface" can be met by the many digital interfaces disclosed, most notably digital outputs 112g and 112h in combination with the controller 105 and the interface 105a. "There are two digital output 112g and 112h. Output 112g may be used for sending decompressed digital data, for example, to a digital television receiver" (Page 16). The claimed step "displaying a message showing that a recording mode of a program recorded on a recording medium loaded in said reproducing apparatus indicates an analog recording or a digital recording" is met by the controller 105. "Controller 105 is a microprocessor which preferably runs a user control program and allows a user to access and control the multi-source recorder player 100" (Page 13). "Of the three analog outputs, output 112a may be set by default in the setup page 300, shown in Fig. 3, to receive the control screens which are described below with respect to the user control section shown in Figs. 2-11" (Page 16). Browne fails

Art Unit: 2614

to explicitly disclose "displaying a message showing that a recording mode of a program recorded on a recording medium loaded in said reproducing apparatus indicates an analog recording or a digital recording". Chihara teaches displaying information of the mode of the recorded program, which would indicate whether the signal is analog or digital so as to provide the user with information regarding the recording (Figure 9, Col 7, Lines 21-31). Consequently, it would have been obvious to one of ordinary skill in the art to modify Browne with displaying information of the mode of the recorded program so as to provide the user with information regarding the recording. The combined teaching fails to explicitly disclose the displaying of an alarm or "message" if the user selects an input/out that is inconsistent with the mode of the recorder/reproducer. However, it is submitted that it would have been clearly obvious to one of ordinary skill in the art to modify the combined teaching with the displaying of an alarm or "message" if the user selects an input/out that is inconsistent with the mode of the recorder/reproducer so as to notify the user of any problem that may arise in program recording/reproduction.

In regard to claim 70, the aforementioned combined teaching of claim 69 discloses a large capacity, random access, multi-source audio and video recorder player which is capable of receiving a plurality of simultaneous input signals and which allows a user to view and/or record selected ones of the plurality of input signals. The reference fails to explicitly disclose the displaying of an alarm or "message" if the user selects an input/out that is inconsistent with the mode of the recorder/reproducer. However, it is submitted that it would have

Art Unit: 2614

been clearly obvious to one of ordinary skill in the art to modify the combined teaching with the displaying of an alarm or "message" if the user selects an input/out that is inconsistent with the mode of the recorder/reproducer so as to notify the user of any problem that may arise in program recording/reproduction.

In regard to claim 71, the claimed step of "receiving a digital broadcasting signal constructed by a transport stream in which video data and audio data have been compressed and multiplexed" is met by the received DBS signal. The DBS signal is intrinsically is compressed and multiplexed. The claimed step of "decoding said received digital broadcasting signal" can be met by met by the A/D converter 102, the compressors 103, the decompressors 106 or the D/A converters 110. The claimed step of "receiving the transport stream from a reproducing apparatus through a digital interface" can be met by the many digital interfaces disclosed, most notably digital outputs 112g and 112h in combination with the controller 105 and the interface 105a. "There are two digital output 112g and 112h. Output 112g may be used for sending decompressed digital data, for example, to a digital television receiver" (Page 16). The claimed steps "of displaying the information associated with the program recorded on the recording medium loaded in said reproducing apparatus by a predetermined format" is met by the controller 105. "Controller 105 is a microprocessor which preferably runs a user control program and allows a user to access and control the multi-source recorder player 100" (Page 13). "Of the three analog outputs, output 112a may be set by default in the setup page 300, shown in Fig. 3, to receive the control screens which are described below with respect to the user control section

Art Unit: 2614

shown in Figs. 2-11" (Page 16). The source column in the stored program list screen 600 shown in Figure 6 indicates the originating source of the signal.

Browne fails to explicitly disclose "displaying a message showing that a recording mode of a program recorded on a recording medium loaded in said reproducing apparatus indicates an analog recording or a digital recording". Chihara teaches displaying information of the mode of the recorded program, which would indicate whether the signal is analog or digital so as to provide the user with information regarding the recording (Figure 9, Col 7, Lines 21-31). Consequently, it would have been obvious to one of ordinary skill in the art to modify Browne with displaying information of the mode of the recorded program so as to provide the user with information regarding the recording. The combined teaching fails to explicitly disclose the displaying of an alarm or "message" if the user selects an input/out that is inconsistent with the mode of the recorder/reproducer. However, it is submitted that it would have been clearly obvious to one of ordinary skill in the art to modify the combined teaching with the displaying of an alarm or "message" if the user selects an input/out that is inconsistent with the mode of the recorder/reproducer so as to notify the user of any problem that may arise in program recording/reproduction.

In regard to claim 72, the claimed step of "receiving a digital broadcasting signal constructed by a transport stream in which video data and audio data have been compressed and multiplexed" is met by the received DBS signal. The DBS signal is intrinsically is compressed and multiplexed. The claimed step of "decoding said received digital broadcasting signal" can be met by met by the

Art Unit: 2614

A/D converter 102, the compressors 103, the decompressors 106 or the D/A converters 110. The claimed step of "receiving the transport stream from a reproducing apparatus through a digital interface" can be met by the many digital interfaces disclosed, most notably digital outputs 112g and 112h in combination with the controller 105 and the interface 105a. "There are two digital output 112g and 112h. Output 112g may be used for sending decompressed digital data, for example, to a digital television receiver" (Page 16). The claimed steps "of displaying the information associated with the program recorded on the recording medium loaded in said reproducing apparatus by a predetermined format" is met by the controller 105. "Controller 105 is a microprocessor which preferably runs a user control program and allows a user to access and control the multi-source recorder player 100" (Page 13). "Of the three analog outputs, output 112a may be set by default in the setup page 300, shown in Fig. 3, to receive the control screens which are described below with respect to the user control section shown in Figs. 2-11" (Page 16). The source column in the stored program list screen 600 shown in Figure 6 indicates the originating source of the signal. Although not displayed in Figure 6, DBS (direct broadcast satellite) is a selectable source. DBS indicates a digital signal. Browne fails to explicitly disclose "displaying a message showing that a recording mode of a program recorded on a recording medium loaded in said reproducing apparatus indicates an analog recording or a digital recording". Chihara teaches displaying information of the mode of the recorded program, which would indicate whether the signal is analog or digital so as to provide the user with information regarding

Art Unit: 2614

the recording (Figure 9, Col 7, Lines 21-31). Consequently, it would have been obvious to one of ordinary skill in the art to modify Browne with displaying information of the mode of the recorded program so as to provide the user with information regarding the recording. The combined teaching fails to explicitly disclose the displaying of an alarm or "message" if the user selects an input/out that is inconsistent with the mode of the recorder/reproducer. However, it is submitted that it would have been clearly obvious to one of ordinary skill in the art to modify the combined teaching with the displaying of an alarm or "message" if the user selects an input/out that is inconsistent with the mode of the recorder/reproducer so as to notify the user of any problem that may arise in program recording/reproduction.

4. Claims 34, 45, 50, 61 and 66 are rejected under 35 U.S.C. 103(a) as being unpatentable over Browne et al. in view of Lenihan et al. and further in view of Chihara and further in view of Yuen et al (US Pat No 6,147,715).

In regard to claims 34, 45, 50, 61 and 66, the aforementioned combined teaching of claim 31 discloses a large capacity, random access, multi-source audio and video recorder player which is capable of receiving a plurality of simultaneous input signals and which allows a user to view and/or record selected ones of the plurality of input signals. The combined teaching fails to explicitly disclose information associated with a program that is "overlapped" or overlaid to a reproduction signal. Yuen et al. teaches information associated with a program that is "overlapped" or overlaid to a reproduction signal so as to provide the user with information in a convenient fashion. "A PIP chip is

Art Unit: 2614

operatively connected to the guide switch and the program source switch such that in an active mode the PIP chip displays on a television screen a PIP window displaying the moving, real time images of a selected program overlaid on a background comprising selected guide information" (Col 1, Lines 59-64).

Consequently, it would have been obvious to one of ordinary skill in the art to implement the combined teaching with information associated with a program that is "overlapped" or overlaid to a reproduction signal so as to provide the user with information in a convenient fashion.

5. Claims 35-37, 39, 53-55 and 57 are rejected under 35 U.S.C. 103(a) as being unpatentable over Browne et al. in view of Chihara.

In regard to claim 35, the claimed step of "receiving a digital broadcasting signal constructed by a transport stream in which video data and audio data have been compressed and multiplexed" is met by the received DBS signal. The DBS signal is intrinsically is compressed and multiplexed. The claimed step of "decoding said received digital broadcasting signal" can be met by met by the A/D converter 102, the compressors 103, the decompressors 106 or the D/A converters 110. The claimed step of "receiving the transport stream from a reproducing apparatus through a digital interface" can be met by the many digital interfaces disclosed, most notably digital outputs 112g and 112h in combination with the controller 105 and the interface 105a. "There are two digital output 112g and 112h. Output 112g may be used for sending decompressed digital data, for example, to a digital television receiver" (Page 16). Browne fails to explicitly disclose "displaying a message showing that a recording mode of a program



Art Unit: 2614

recorded on a recording medium loaded in said reproducing apparatus indicates an analog recording or a digital recording". Chihara teaches displaying information of the mode of the recorded program, which would indicate whether the signal is analog or digital so as to provide the user with information regarding the recording (Figure 9, Col 7, Lines 21-31). Consequently, it would have been obvious to one of ordinary skill in the art to modify Browne with displaying information of the mode of the recorded program so as to provide the user with information regarding the recording.

Claim 36 is met by the stored program list screen 600 illustrated in Figure 6 of Browne. It is noted that the examiner interprets the claim to be written in the alternative, such that a channel number, a program name, a genre, a date of the recording, or a recording time may meet the claimed limitation. The stored program list screen 600 clearly shows the channel number, the program name, date of the recording, and the recording time.

In regard to claim 37, the recording position is inherent to the information displayed. In order for the programs to be retrieved, there must there be position information.

Claim 39 is met by that discussed above for claim 35.

In regard to claim 53, the claimed step of "receiving a digital broadcasting signal constructed by a transport stream in which video data and audio data have been compressed and multiplexed" is met by the received DBS signal. The DBS signal is intrinsically is compressed and multiplexed. The claimed step of "decoding said received digital broadcasting signal" can be met by met by the

Art Unit: 2614

A/D converter 102, the compressors 103, the decompressors 106 or the D/A converters 110. The claimed step of "receiving the transport stream from a reproducing apparatus through a digital interface" can be met by the many digital interfaces disclosed, most notably digital outputs 112g and 112h in combination with the controller 105 and the interface 105a. "There are two digital output 112g and 112h. Output 112g may be used for sending decompressed digital data, for example, to a digital television receiver" (Page 16). Browne fails to explicitly disclose "displaying a message showing that a recording mode of a program recorded on a recording medium loaded in said reproducing apparatus indicates an analog recording or a digital recording". Chihara teaches displaying information of the mode of the recorded program, which would indicate whether the signal is analog or digital so as to provide the user with information regarding the recording (Figure 9, Col 7, Lines 21-31). Consequently, it would have been obvious to one of ordinary skill in the art to modify Browne with displaying information of the mode of the recorded program so as to provide the user with information regarding the recording.

Claim 54 is met by the stored program list screen 600 illustrated in Figure 6. It is noted that the examiner interprets the claim to be written in the alternative, such that a channel number, a program name, a genre, a date of the recording, or a recording time may meet the claimed limitation. The stored program list screen 600 clearly shows the channel number, the program name, date of the recording, and the recording time.

In regard to claim 55, the recording position is inherent to the information displayed. In order for the programs to be retrieved, there must there be position information.

Claim 57 is met by that discussed above for claim 53.

Claim 38 is rejected under 35 U.S.C. 103(a) as being unpatentable over Browne et al. in view of Chihara and further in view of Yuen et al.

In regard to claim 38, the combination of Browne and Chihara discloses a large capacity, random access, multi-source audio and video recorder player which is capable of receiving a plurality of simultaneous input signals and which allows a user to view and/or record selected ones of the plurality of input signals. Brown et al. fails to explicitly disclose information associated with a program that is "overlapped" or overlaid to a reproduction signal. Yuen et al. teaches information associated with a program that is "overlapped" or overlaid to a reproduction signal so as to provide the user with information in a convenient fashion. "A PIP chip is operatively connected to the guide switch and the program source switch such that in an active mode the PIP chip displays on a television screen a PIP window displaying the moving, real time images of a selected program overlaid on a background comprising selected guide information" (Col 1, Lines 59-64). Consequently, it would have been obvious to one of ordinary skill in the art to implement the combined teaching with information associated with a program that is "overlapped" or overlaid to a reproduction signal so as to provide the user with information in a convenient fashion.

Claim 56 is rejected under 35 U.S.C. 103(a) as being unpatentable over Browne et al. in view of Chihara and further in view of Yuen et al (US Pat No 6,147,715).

In regard to claim 56, the aforementioned combined teaching of claim 53 discloses a large capacity, random access, multi-source audio and video recorder player which is capable of receiving a plurality of simultaneous input signals and which allows a user to view and/or record selected ones of the plurality of input signals. The combined teaching fails to explicitly disclose information associated with a program that is "overlapped" or overlaid to a reproduction signal. Yuen et al. teaches information associated with a program that is "overlapped" or overlaid to a reproduction signal so as to provide the user with information in a convenient fashion. "A PIP chip is operatively connected to the guide switch and the program source switch such that in an active mode the PIP chip displays on a television screen a PIP window displaying the moving, real time images of a selected program overlaid on a background comprising selected guide information" (Col 1, Lines 59-64). Consequently, it would have been obvious to one of ordinary skill in the art to implement the combined teaching with information associated with a program that is "overlapped" or overlaid to a reproduction signal so as to provide the user with information in a convenient fashion.

***Conclusion***

Any inquiry concerning this communication or earlier communications from the examiner should be directed to John Manning whose telephone number is 703-305-0345. The examiner can normally be reached on M-F: 8:00 - 5:30.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, John W Miller can be reached on 703-305-4795. The fax phone number for the organization where this application or proceeding is assigned is 703-872-9306.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

JM  
January 18, 2005

  
**JOHN MILLER**  
**SUPERVISORY PATENT EXAMINER**  
**TECHNOLOGY CENTER 2600**